



PREMA180 & PREMA180+

INFORMATION REQUIREMENTS FOR NRUV'S (EU1253/2014)

Commission Regulation 1253/2014	Using the "reference configuration"	
	ERP Product Information	
Manufacturer	Elta Fans Ltd	
Model	PREMA180	
Declared typology	NRVU BVU - Bidirectional Ventilation Unit	
Drive	Variable Speed Drive	
Heat Recovery System HRS	Recuperative	
Thermal Efficiency EN308	82.6%	Dry Efficiency

	Supply	Extract	
Nominal flow rate	0.134	0.134	m ³ /s
Electric input	0.082	0.081	kW
Internal specific fan power (Ventilation components) SFP _{int}	388	386	W/(m ³ /s)
Face velocity at nominal flow rate	1.05	1.05	m/s
Nominal external pressure DP _{s, ext}	50	50	Pa
Internal pressure drop (Ventilation components) ΔP _{s, int}	142		Pa
Internal pressure drop (Non-ventilation components) ΔP _{s, add}	-		Pa
Fan(s) Overall static Eff	36.6	36.7	%
External leakage rate EN1886	L2		Class rating < than
Filter Class	ePM ₁ 5%	ePM ₁₀ 55%	-
Filter energy performance	106	23	kWh Based on Eurovent 4/21 - 2014
Filter energy classification	A+	A+	Based on Eurovent 4/21 - 2014
Filter dirty visual warning	Pressure control		-
Casing sound power level (L _{wa})	47		dB(A)
Casing sound pressure level	26		dBA @ 3m
Website	www.air-design.com		

T +44 (0)1384 275800

F +44 (0)1384 275810

E SALES@AIR-DESIGN.COM

W AIR-DESIGN.COM

46 THIRD AVENUE | PENNETT TRADING ESTATE
KINGSWINFORD | WEST MIDLANDS | DY6 7US | **UK**

PREMA180 ECODESIGN